

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re Patent Application of: )  
**DENYER ET AL.** )  
 )  
Serial No. **Not Yet Assigned** )  
 )  
Filing Date: **Herewith** )  
 )  
For: **IMAGE SENSORS WITH MULTIPLE** )  
**INTEGRATION/READ CYCLES** )  
\_\_\_\_\_)  
I HEREBY CERTIFY THIS PAPER OR FEE IS BEING  
DEPOSITED WITH THE U.S. POSTAL SERVICE  
"EXPRESS MAIL POST OFFICE TO ADDRESSEE"  
SERVICE UNDER 37 CFR 1.10 ON THE DATE  
INDICATED BELOW AND IS ADDRESSED TO:  
BOX PATENT APPLICATIONS, ASSISTANT  
COMMISSIONER FOR PATENTS, WASHINGTON,  
D.C. 20231.  
EXPRESS MAIL NO: EL747059158US  
DATE OF DEPOSIT: June 25, 2001  
NAME: Kristin Thanski  
SIGNATURE: Kristin Thanski

**PRELIMINARY AMENDMENT**

Director, U.S. Patent and Trademark Office  
Washington, D.C. 20231

Sir:

Prior to the calculation of fees and examination of  
the present application, please enter the amendments and  
remarks set out below.

**In the Drawings:**

Submitted herewith is a request for a proposed  
drawing modification as indicated in red ink to label FIG.  
1(a) as prior art.

**In the Claims:**

Please cancel Claims 1 to 11.

Please add new Claims 12 to 31.

12. A method of operating a solid state image  
sensing array comprising a plurality of active pixels, the  
method comprising:

In re Patent Application of:  
**DENYER ET AL.**  
Serial No. **Not Yet Assigned**  
Filed: **Herewith**

---

resetting each pixel;

reading a first output from each pixel after a first period of time to obtain a first set of image data having a first dynamic range;

reading a second output from each pixel after a second period of time and without resetting each pixel to obtain a second set of image data having a second dynamic range; and

combining the first and second sets of image data to obtain a resultant set of image data having a dynamic range different from the first and second dynamic ranges.

13. A method according to Claim 12, further comprising:

reading at least a third output from each pixel after at least a third period of time and without resetting each pixel to obtain a third set of image data having a third dynamic range; and

combining at least the first, second and third sets of image data to obtain a resultant set of image data having a dynamic range different from the first, second and third dynamic ranges.

14. A method according to Claim 12, wherein the first and second periods of time are selected to be an integer multiple of a predetermined lighting flicker period.

15. A method according to Claim 12, wherein the image sensing array remains continuously exposed to incident light when the resetting is performed, and when the reading of the first and second outputs are performed.

In re Patent Application of:  
**DENYER ET AL.**  
Serial No. **Not Yet Assigned**  
Filed: **Herewith**

---

16. A method of operating a solid state image sensing array comprising a plurality of active pixels, the method comprising:

resetting and immediately reading a preliminary output from each pixel; and

reading a first output from each pixel after a first period of time.

17. A method according to Claim 16, further comprising determining a difference between the preliminary outputs and the first outputs to obtain a set of image data substantially free of noise components represented by the preliminary outputs.

18. A method according to Claim 16, wherein the first period of time is selected to be an integer multiple of a predetermined lighting flicker period.

19. A method according to Claim 16, wherein the image sensing array remains continuously exposed to incident light when the resetting is performed, and when the reading of the preliminary and first outputs are performed.

20. A method according to Claim 16, further comprising:

reading a second output from each pixel after a second period of time and without resetting each pixel to obtain a second set of image data having a second dynamic range; and

determining a difference between the preliminary outputs and each of the first, second and any subsequent

In re Patent Application of:  
**DENYER ET AL.**  
Serial No. **Not Yet Assigned**  
Filed: **Herewith**

---

outputs to obtain a plurality of sets of image data each of which is substantially free of noise components represented by the preliminary outputs.

21. A solid state image sensor comprising:  
a plurality of active pixels;  
a vertical shift register connected to rows of said plurality of active pixels;  
a horizontal shift register connected to columns of said plurality of active pixels; and  
scanning circuitry connected to said vertical and horizontal shift registers for reading said plurality of active pixels by resetting each pixel, reading a first output from each pixel after a first period of time to obtain a first set of image data having a first dynamic range, reading a second output from each pixel after a second period of time and without resetting each pixel to obtain a second set of image data having a second dynamic range, and combining the first and second sets of image data to obtain a resultant set of image data having a dynamic range different from the first and second dynamic ranges.

22. A solid state image sensor according to Claim 21, wherein said scanning circuitry further reads at least a third output from each pixel after at least a third period of time and without resetting each pixel to obtain a third set of image data having a third dynamic range, and combines at least the first, second and third sets of image data to obtain a resultant set of image data having a dynamic range different from the first, second and third dynamic ranges.

In re Patent Application of:  
**DENYER ET AL.**  
Serial No. **Not Yet Assigned**  
Filed: **Herewith**

---

23. A solid state image sensor according to Claim 21, wherein the first and second periods of time are selected to be an integer multiple of a lighting flicker period.

24. A solid state image sensor to Claim 21, wherein said image sensing array remains continuously exposed to incident light when the resetting is performed, and when the reading of the first and second outputs are performed.

25. A solid state image sensor to Claim 21, wherein said plurality of active pixels, said vertical and horizontal shift registers and said scanning circuitry are incorporated into a camera.

26. A solid state image sensor comprising:  
a plurality of active pixels;  
a vertical shift register connected to rows of said plurality of active pixels;  
a horizontal shift register connected to columns of said plurality of active pixels; and  
scanning circuitry connected to said vertical and horizontal shift registers for reading said plurality of active pixels by resetting and immediately reading a preliminary output from each pixel, and reading a first output from each pixel after a first period of time.

27. A solid state image sensor according to Claim 26, wherein said scanning circuitry determines a difference between the preliminary outputs and the first outputs to obtain a set of image data substantially free of noise components represented by the preliminary outputs.

In re Patent Application of:  
**DENYER ET AL.**  
Serial No. **Not Yet Assigned**  
Filed: **Herewith**

---

28. A solid state image sensor according to Claim 26, wherein the first period of time is selected to be an integer multiple of a predetermined lighting flicker period.

29. A solid state image sensor according to Claim 26, wherein said image sensing array remains continuously exposed to incident light when the resetting is performed, and when the reading of the preliminary and first outputs are performed.

30. A solid state image sensor according to Claim 26, wherein said scanning circuitry further reads a second output from each pixel after a second period of time and without resetting each pixel to obtain a second set of image data having a second dynamic range, and determines a difference between the preliminary outputs and each of the first, second and any subsequent outputs to obtain a plurality of sets of image data each of which is substantially free of noise components represented by the preliminary outputs.

31. A solid state image sensor to Claim 26, wherein said plurality of active pixels, said vertical and horizontal shift registers and said scanning circuitry are incorporated into a camera.

#### REMARKS


It is believed that all of the claims are patentable over the prior art. For better readability and the Examiner's convenience, the newly submitted claims differ from the translated counterpart claims which are being canceled. The newly submitted claims do not represent changes or amendments

In re Patent Application of:  
**DENYER ET AL.**  
Serial No. **Not Yet Assigned**  
Filed: **Herewith**

---

that narrow the claim scope for any reason related to the statutory requirements for patentability. Accordingly, after the Examiner completes a thorough examination and finds the claims patentable, a Notice of Allowance is respectfully requested in due course. Should the Examiner determine any minor informalities that need to be addressed, he is encouraged to contact the undersigned attorney at the telephone number below.

Respectfully submitted,

  
\_\_\_\_\_  
MICHAEL W. TAYLOR  
Reg. No. 43,182  
Allen, Dyer, Doppelt, Milbrath  
& Gilchrist, P.A.  
255 S. Orange Avenue, Suite 1401  
Post Office Box 3791  
Orlando, Florida 32802  
407-841-2330  
407-841-2343 fax  
Attorneys for Applicants




FIG. 1(a)  
(PRIOR ART)




FIG. 1(b)




FIG. 1(c)